

Performance

Pressure (bar)	Nozzle	Radius (m)	Flow (l/min)	■ (mm/h)	▲ (mm/h)
2,0	0,75	5,1	2,8	5,67	6,54
	1,0	6,0	3,4	6,46	7,46
	1,5	6,9	5,3	6,68	7,71
	2,0	7,5	6,8	7,25	8,38
	3,0	8,4	10,2	8,67	10,01
2,8	0,75	5,4	3,0	6,17	7,13
	1,0	6,3	4,5	6,80	7,85
	1,5	7,2	6,4	7,41	8,55
	2,0	8,1	8,0	7,32	8,45
	3,0	9,0	11,4	8,44	9,75
3,5	0,75	5,4	3,4	7,00	8,08
	1,0	6,3	4,9	7,41	8,55
	1,5	7,2	7,2	8,33	9,62
	2,0	8,1	9,1	8,32	9,61
	3,0	9,0	12,5	9,26	10,69

- Precipitation rates for "square" spacing and full circle operation
 - ▲ Precipitation rates for "triangular" spacing and full circle operation
 - Spacing based on 100% of radius
- The data indicated is the result of tests conducted in zero wind conditions

No special tool required

All arc adjustments made from the top with a standard screwdriver reduces set up time



Codification

Code	Description
430R	430R Rotor 1/2", 40°-360