

SL Series



2", 4", 6" models

½" female threaded

Compatible nozzles: I-Pro, Pro-Van, Rotary Nozzles, Special nozzles

The SL series is a family of sprayheads with a compact design that guarantees flexibility, reliability and good value for money. It is ideal for small and medium-sized systems and is adaptable to both fixed and variable arc nozzles.

Features

One-piece molded body adds durability

Pressure-activated seal reduces flow-by during pop up and keeps away from stem during retraction

Heavy-duty, stainless steel retract spring ensures positive pop down

Nozzles with matched precipitation rate

The arc can be adjusted even when the sprinkler is running

Available with pre-installed Pro-Van nozzles with radius: 10', 12', 15', 17'

Additional Features

Removable nozzles, screen and internal components for flushing and servicing

Debris labels on models without nozzles for easy flushing

Specifications

Exposed diameter: 3,18 cm

Recommended working pressure: 1,5-3,0 bar

Flushing:

- from 0 to 0,7 bar: 1,9 l/min
- above 0,7 bar: 0 l/min (flow range null)

Body height:

- SL200: 10,5 cm
- SL400: 15,5 cm
- SL600: 20,6 cm
- I-PRO1200-SI: 40,5 cm

Options

Integrated check valve that prevents drainage and hence wasting water for a difference in height of up to 2,10 m



Codification

SL Series body only

Code	Description
SLP200	SL 2" Fixed Sprayhead – riser height 5 cm, without nozzles (body only)
SLP400	SL 4" Fixed Sprayhead – riser height 10 cm, without nozzles (body only)
SLP600	SL 6" Fixed Sprayhead – riser height 15 cm, without nozzles (body only)
SL-CV	SL Check Valve

SL Series with Pro Van nozzle preassembled 10, Radius 2,7-3,0m, Trajectory 10°

Code	Description
SLP210	SL 2" Fixed Sprayhead – riser height 5 cm, with Pro Van nozzles 10°
SLP410	SL 4" Fixed Sprayhead – riser height 10 cm, with Pro Van nozzles 10°

SL Series with Pro Van nozzle preassembled 12, Radius 3,0-3,7m, Trajectory 15°

Code	Description
SLP212	SL 2" Fixed Sprayhead – riser height 5 cm, with Pro Van nozzles 15°
SLP412	SL 4" Fixed Sprayhead – riser height 10 cm, with Pro Van nozzles 15°

SL Series with Pro Van nozzle preassembled 15, Radius 4,1-4,6m, Trajectory 20°

Code	Description
SLP215	SL 2" Fixed Sprayhead – riser height 5 cm, with Pro Van nozzles 20°
SLP415	SL 4" Fixed Sprayhead – riser height 10 cm, with Pro Van nozzles 20°

SL Series with Pro Van nozzle preassembled 17, Radius 4,3-5,1m Trajectory 26°

Code	Description
SLP217	SL 2" Fixed Sprayhead – riser height 5 cm, with Pro Van nozzles 26°
SLP417	SL 4" Fixed Sprayhead – riser height 10 cm, with Pro Van nozzles 26°