

Special Nozzles



9', 15' models (2,7 & 4,5 m models)

Female-threaded compatible with I-Pro and SL sprayheads

Precipitation rates balanced with the I-Pro fixed arc nozzles



The range of special Irritrol nozzles has been designed so that they can be adapted to the most varied situations and they can also be arranged at any point in the system

Performance

Code	2,7 m RADIUS			4,5 m RADIUS		
	bar	WxL (m)	l/min	bar	WxL (m)	l/min
SS 	1,4	0,9 x 4,9	3,2	1,4	0,9 x 8,5	4,2
	2,0	1,2 x 5,5	3,4	2,0	1,2 x 9,1	4,6
	2,7	1,5 x 6,1	3,7	2,7	1,5 x 9,8	5,1
CS 	1,4	0,9 x 4,9	3,2	1,4	0,9 x 8,5	4,2
	2,0	1,2 x 5,5	3,4	2,0	1,2 x 9,1	4,6
	2,7	1,5 x 6,1	3,7	2,7	1,5 x 9,8	5,1
ES 	1,4	0,9 x 2,4	1,6	1,4	0,9 x 4,3	2,0
	2,0	1,2 x 2,7	1,7	2,0	1,2 x 4,6	2,3
	2,7	1,5 x 3,0	1,8	2,7	1,5 x 5,2	2,6

W = width L = length

The values given in these charts are representative of the throw for each nozzle at each pressure point

Features

Suitable for square patterns:

- SS = side strip
- CS = central strip
- ES = end strip

Filter included

Radius reduction up to 25%

Specifications

Pattern covered: 0,9x4,3 – 1,5x9,8 m

Flow Range: 1,6 – 5,1 l/min

Recommended operating pressure:
1,4 – 2,7 bar

Codification

Code	Description
IPN-9SST	Series 9 Special nozzle – side strip
IPN-9CST	Series 9 Special nozzle – central strip
IPN-9EST	Series 9 Special nozzle – end strip
IPN-15SST	Series 15 Special nozzle – side strip
IPN-15CST	Series 15 Special nozzle – central strip
IPN-15EST	Series 15 Special nozzle – end strip